

KRYPTON

Description Krypton is a rare atmospheric gas which is odorless, colorless, tasteless, nontoxic, monatomic and chemically inert. The concentration of Krypton in the atmosphere by volume percent is 1.1×10^{-4} . Krypton is principally shipped and used in gaseous form for excimer lasers, light bulbs, window insulation, sputtering deposition and R & D laboratory research. Linde Material Safety Data Sheets (MSDS) are available for Krypton gas and should be used as guidelines in regard to first aid, methods of storage, handling and general use of Krypton.

Purity Specifications

Contaminant	Research Grade 99.999%*	UHP Grade 99.995%*
Argon (Ar)	2.0 ppm	2.0 ppm
Carbon Dioxide (CO ₂)	0.5 ppm	1.0 ppm
Carbon Monoxide (CO)	1.0 ppm	N/A
Carbon Tetrafluoride (CF ₄)	0.5 ppm	1.0 ppm
Hydrogen (H ₂)	0.5 ppm	2.0 ppm
Nitrogen (N ₂)	2.0 ppm	5.0 ppm
Oxygen (O ₂)	0.5 ppm	1.0 ppm
Total Hydrocarbon (THC) as Methane	0.5 ppm	1.0 ppm
Water (H ₂ O)	0.5 ppm	1.0 ppm
Xenon (Xe)	5.0 ppm	25.0 ppm

* Maximum Impurity Levels
Note: Higher purities are available upon request.

Cylinder Information

Purity	Cylinder Size*	Internal Volume Water Liters	Valve Outlet*	Volume Liters	Gross Weight Lbs/Kg	Pressure Psig/Bar
Research Grade	1	49	580	10000	213 / 97	2300 / 160
	2	44	580	5000	155 / 70	1350 / 94
	3	16	580	2000	63 / 29	1500 / 104
	4	8	580	1000	31 / 14	1450 / 101
	5	3	580	500	16 / 7	2000 / 139
	LB	0.42	580/170	50	6 / 3	1400 / 98
UHP Grade	1	49	580	10000	213 / 97	2300 / 160
	2	44	580	5000	155 / 70	1350 / 94
	3	16	580	2000	63 / 29	1500 / 104
	4	8	580	1000	31 / 14	1450 / 101
	5	3	580	500	16 / 7	2000 / 139
	LB	0.42	580/170	50	6 / 3	1400 / 98
Non-Refillable Cylinders	D1	3.7	580	400	16 / 7	1300 / 91
	D2	2.4	580	200	11 / 5	1050 / 73
	D2	2.4	580	100	10 / 5	575 / 41
	D3	1.0	580	50	7 / 3	675 / 48
	D3	1.0	580	25	6 / 3	350 / 25
	D7	1.1	580	20	3 / 1	240 / 18
	D7	1.1	580	12	3 / 1	140 / 11

* Additional cylinder sizes and/or valve outlets are available upon request.

Physical Constants

Chemical name	Kr	
Molecular weight	83.80	
Density of the gas at 70°F (+21.1° C), 1 atm	0.2172 lb/ft ³ , 3.479 kg/m ³	
Specific gravity of the gas at 70°F (+21.1° C), 1 atm	2.899	
Specific volume of the gas at 70°F (+21.1° C), 1 atm	4.604 ft ³ /lb, 0.287 m ³ /kg	
Boiling point at 1 atm	-244.0°F, -153.4°C	
Melting point at 1 atm	-251°F, -157°C	
Critical temperature at 1 atm	-82.8°F, -63.8°C	
Critical pressure	798.0 psia, 55.02 bar	
Critical density	56.7 lb/ft ³ , 908 kg/m ³	
Triple point	-251.3°F, -157.4°C	
Latent heat of vaporization at boiling point	46.2 Btu/lb, 107.5 kJ/kg	
Latent heat of fusion at triple point	8.41 Btu/lb, 19.57 kJ/kg	
Specific heat of the gas at 70°F (+21.1° C), 1 atm	Cp	0.060 Btu/(lb) (°F) 0.251 kJ/(kg) (°C)
	Cv	0.035 Btu/(lb) (°F) 0.146 kJ/(kg) (°C)

Shipping Data

Synonyms	Kr
CAS Register Number	7439-90-9
DOT Classification	Nonflammable gas
DOT Label	Nonflammable gas
Transport Canada Classification	2.2
Substance Identification (SI)	1056
UN Number	UN 1056
Hazards	High Pressure and suffocation
Toxicity (TLV)	Asphyxiant
Flammability Range (in air)	Nonflammable gas
Odor	None

Linde Electronics and Specialty Gases

One Greenwich Street, Suite 100, Stewartsville, NJ 08886 USA
 Phone 908-329-9700, Fax 908-329-9740, www.lindeus.com

Linde LLC is a member of the Linde Group. Linde is a trading name used by companies within The Linde Group. The Linde logo and the words Linde and SPECTRA, HiQ®, REDLINE®, BASELINE®, SPECTRA-SEAL®, ECOCYL® AND VERISEQ® are trademarks of The Linde Group. Copyright The Linde Group 2010.